



PALING
TRANSPORTER LTD.

Drivetrain			Standard on LT60225	
			Caterpillar C9 Dana - T40000	
Engine	Manufacture - Type Designation		Caterpillar - C9	
	Fuel - type of engine		Diesel	
	Rating ISO 3046 - at revs	rpm	1800 rpm	
	Peak torque ISO 3046 - at revs	rpm	1400 rpm	
	Number of cylinders - displacement	inch ³	6 - 537	
	Fuel consumption, normal driving	g/hr	6.3	
Gearbox	Manufacture - Type Designation		Dana - T40000	
	Clutch, type		Full Powershift	
	Gearbox, type		Torque Converter	
	Number of gears, forward - reverse		4 - 4	
Alternator	Type - power		AC - 1560 W	
Starting battery	Voltage - capacity		2x12 V - 1280 CCA	
Driving axle	Manufacture - Type		Axletech-Differential	
Noise level	LpAZ (inside) Sprit Delta	dB(A)	75 max	
	LWA (outside)	dB(A)	---	

Performance - Caterpillar C9 with Dana T40000 313 kW Transmission				
Lifting Speed	Unloaded	ft/s	1.3	
	at rated load	ft/s	1.2	
Lowering speed	Unloaded	ft/s	0.7	
	at rated load	ft/s	1.3	
Traveling speed - forward - reverse	Unloaded	m/h	20	
	at rated load	m/h	15	
Gradeability	Max	Unloaded	%	45%
		at rated load	%	35%
	At 2 km/h	Unloaded	%	45%
		at rated load	%	31%
Maintenance Intervals on Lift Truck				500 hrs

Dimensions				
Lift Capacity	Rated		60 ton	
	Load Center		48"	
Truck	Length - without forks		323"	
	Width		149"	
	Height, Basic Machine		168"	
	Seat Height		119"	
	Distance between center of front axle - front face of forks		51"	
	Wheel base		225"	
	Track (c-c) front to back width		106"/ 93"	
	Turning radius outer		334"	
	Turning radius inner		88"	
	Ground clearance min.		8"	
	Min. aisle width for 90 deg steering		20.5'	



PALING

TRANSPORTER LTD.

Standard Mast	Lifting Height		150"
	Mast height min.		168"
	Mast height max.		240"
	Mast tilting forward - backward		5° - 7°
	Ground clearance min.		8"
Forks	Width		12"
	Thickness		6.5"
	Length of fork arm		96"
Weight	Service Weight		122375 lbs
	Axle Load - Drive	Without load	51645 lbs
		With load	224445 lbs
	Axle Load - Steer	Without load	70730 lbs
		With load	17930 lbs
Wheels	Type		Pneumatic
	Dimensions - Front/Rear		18.00-R25 / 18.00-R25
	Number of wheels, front-rear		4 - 2
	Pressure		130 lbs/inch ²
Steering System	Type - Manoeuvring		Orbitrol steering valve with tilt steering column & steering wheel
Service Brake System	Type - affected wheels		Wet disc brakes - drive axle (4) wheels
Parking Brake System	Type - affected wheels		Rear (2) wheels
Misc.	Hydraulic pressure - max.		2500 lbs/inch ²
	Hydraulic fluid volume		110 gallon
	Fuel volume		110 gallon